

ALEXGRAVIATO



**Textured Decorative Finish for Interior and Exterior
Use Containing Quartz Aggregate to give Special Effect**

Description

ALEXGRAVIATO is a quartz scratchable wall facing for interiors and exteriors made up to siliceous aggregates granular quartz, synthetic resins in emulsion pigments and various additives.

Uses

- Used on internal and external walls.
- Used in surfaces already painted by normal paints.
- Used for gypsum blocks.
- Used for board after treating with ALEXPRIME PL.

Advantages

- Highly resistance to cracks due to its elasticity.
- Used for interior and exterior.
- Easy for use.
- Non toxic.
- Economic.
- Color retention.
- Weather resistance.
- Can be wash.
- Humidity and water resistance.

Properties

Colour	White	
Solid content	88.16 % by volume	
Drying time	Surface dry	30 min
	Complete dry	4-6 hr

Guide to application

- Prepare a good clean structural surface for bonding by removing all loose materials (dust ,oil grease or others).
- Traces of oil, grease and curing compounds should be removed by chiseling the affected part.
- **ALEXGRAVIATO** diluted by 0.5 lit of clean water.
- Trowel can be used for applying.

Coverage:

ALEXGRAVIATO is approximately covers 3.5 kg: 4.0 kg / m² on ideal surface conditions

Packing:

Is supplied in 5 Kg, 10Kg& 20 Kg.

Storage:

Store out of direct sunlight, clear of the Ground on pallets protected from rainfall
Avoid excessive compaction and protect from extremes of temperatures.

Shelf life:

Up to 12 months if stored in unopened Containers at 25 °c according to the manufactured Instructions.

Safety precautions:

- Avoid contact with eyes, mouth, and skin.
- Treat splashes to skin and eyes immediately,
- If accidentally ingested seek medical attention.
- Product is flammable.

Guarantee:

All precaution is taken in manufacture of each product to comply with the standard of each material.
The data sheet for each product for information only and may be corrected and no liability is accepted for it.
The results may have variation because the method of their use condition under which they are applied cannot be anticipated.

Technical Service:

For any technical advice for using the **ALEXCHEM** contact the technical office.

HEAD OFFICE:

33 Elamgad St, Miami, Alexandria
www.alexchem.net
info@alexchem.net
Tel/Fax: +203-5566791
Mob: +20173745566

FACTORY:

ELNahda, Karnak-Amraya
Tel: +203-9680828
Fax: +203-9680830