

ALEXQUICK1035



Quick Setting Waterproofing Compound

Description

ALEXQUICK1035 is a quick setting waterproofing Compound, rapid hardening when mixing with cement to stop running water.

Uses

- To stop running water.
- For fixing bolts and anchors in concrete.
- Used for closing water in rapid repair.
- Cement setting accelerater.

Advantages

- When early strength is required.
- Hardens in 10-35 seconds.
- Easily used and fast applied.

Properties

Colour	Viscous Clear liquid	
Specific Gravity	1.35 kg/lit	20 °C
Setting time	20-35 Seconds	
PH Value	12	
Chloride Content	Nil	

Guide to application

Surface preparation:

- The surface must be clean , free from dust,oils,grease and loose materials, using spraying water to wet the surface.
- Apply two coats of ALEXQUICK1035.

Mixing:

- ALEXQUICK 1035 is poured in a container ,then a fresh cement is added.
- Mix quickly until a plastic consistency is formed.
- Use immediately after mixing.

Coverage:

- Depend on the type of application.

Packing:

It is available in 25 kg

Storage:

Up to 12 months if stored out of direct sun according to manufactured instruction

Safety Precaution:

- ALEXQUICK1035 is non toxic and not harmful while using.
- Remove any contamination from Skin by water and soap.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Guarantee:

All precaution is taken in manufacture of each product to comply with the standard of each material.

The data sheet for each product for information only and may be corrected and no liability is accepted for it.

The results may have variation because the method of their use condition under which they are applied cannot be anticipated.

Technical Service:

For any technical advice for using the **ALEXCHEM** contact the technical office.

HEAD OFFICE:

33 Elamgad St, Miami, Alexandria

www.alexchem.net

info@alexchem.net

Tel/Fax: +203-5566791

Mob: +20173745566

FACTORY:

ELNahda, Karnak-Amraya

Tel: +203-9680828

Fax: +203-9680830