ALEXSHIELD N700

ALEX CHEM

Acrylic Paint For Interior Use

Description

ALEXSHIELD N700 is high quality acrylic emulsion paint. Based on excellent type of acrylic to give a durable matt and smooth finish for interior use.

<u>Uses</u>

Used as paint for:

- Interior dry walls
- Plaster
- •Concrete surface as well as primed wooden surfaces.

Advantages

- Economic.
- Give a durable matt and smooth finish.
- Non toxic.
- Easy for use.

Guide to application

- •Prepare a good clean structural surface for bonding by removing all loose materials (dust ,oil grease or others).
- •Glossy surfaces should be dulled by sanding porous surfaces may be sealed with ALEXSEALAR AR white and should be prepared by ALEXPUTTY before painting.
- •Stir container thoroughly before use and periodically during use.

Properties

Colour	White and other colours on request.
Finish	Matt and Smooth
Density	1.68 ±3 % g/cm ³
N.V. by weight	67 ±1 %
Dust Free	30-40 minutes
Tack Free	1-2 hours
Recoat ability	8 hours
Recommended Thinner	Tap water

Application Method		
	Brush or Roller	Regular Spry
Pressure (atm)	1	3 - 4
Nozzle (orifice)		0.2 - 0.3
Thinner water	Water	Water
Thinning water	5 - 10	15 - 25

Coverage:

ALEXSHIELD N700 is

approximately covers 4.0-6.0 sq.m/kg. Per coat on ideal surface conditions" two coats is recommended".

Packing:

Is supplied in 5kg,10kg&20kg.

Storage:

Store out of direct sunlight, clear of the Ground on pallets protected from rainfall Avoid excessive compaction and protect from extremes of temperatures.

Shelf life:

Up to 12 months if stored in unopened Containers at 25°c according to the manufactured Instructions.

Safety precautions:

- •Avoid contact with eyes, mouth, and skin.
- •Treat splashes to skin and eyes immediately,
- •If accidentally ingested seek medical attention.
- •Product is flammable

Guarantee:

All precaution is taken in manufacture of each product to comply with the standard of each material.

The data sheet for each product for information only and may be corrected and no liability is accepted

for it.

The results may have variation because the method of their use condition under which they are applied cannot be anticipated.

Technical Service:

For any technical advice for using the **ALEXCHEM** contact the technical office.

HEAD OFFICE:

33 Elamgad St, Miami, Alexandria www.alexchem.net

info@alexchem.net

Tel/Fax: +203-5566791 Mob: +20173745566

FACTORY:

ELNahda, Karnak-Amraya

Tel: +203-9680828 Fax: +203-9680830