

# ALEXTOP 110 S.F



## Coloured Cementitious Mortar for Facades

### Description

ALEXTOP 110 S.F is a single component for external facades and internal surfaces. ALEXTOP 110 S.F is easy to apply and use on both dry and wet surfaces.

### Uses

- For external facades.
- For internal surfaces.
- For industrial and commercial facilities.

### Advantages

- Easy to apply (it requires only mixing with water) and available in different colours.
- Use as a final colour layer on the plaster.
- Select of raw materials is subjected to the highest standard of quality control.
- Non toxic, free from chlorides and nitrates.
- It can be applied by using trowels or spraying machine (Tartasha).

### Properties

Colour	Valid in 24 colours and upon request	
Specific Weight	1.7 kg/lit	
Cure Time	25 min	5-35 °C
Thickness	1-2 mm when using trowels	

### Guide to application

#### Surface preparation:

- The surface must be clean, free from dust, oils, grease and loose materials, using spraying water to wet the surface.
- The coloured powder is added gradually to 6-7 lit of water and stir well till reaching the homogenous texture and colour.
- Apply by using trowel or tartasha by using spraying machine.

#### Coverage:

- From 2 to 2.5 kg/m<sup>2</sup> in case of using trowel.
- From 4.50 to 5.50 kg/m<sup>2</sup> in case of using tartasha.

#### Packing:

It is available in 25 kg

#### Storage:

Up to 12 months if stored out of direct sun and away from rain, water. Stored in shaded area.

#### Safety Precaution:

- ALEXTOP 110 S.F is non toxic and not harmful while using.
- Remove any contamination from Skin by water and soap

فرع سلطنة عمان

BRANCH Of Oman

+968 93 20 38 37

فرع مصر

BRANCH OF Egypt

+2 0122 322 3957

المملكة العربية السعودية

BRANCH Kingdom Of Saudi Arabia : Jeddah

+966 566 855 607

+966 533 558 002

VER. 2025